# **POWER YOUR ADVENTURES.**

# **Onan P4500i** NEW

4500 Watt Digital Inverter Gasoline Portable Generator 3700 Running Watts | 4500 Peak Watts



#### **PUSH BUTTON & REMOTE START** • Pull cord backup

- ULTRA QUIET & DURABLE Double-insulated
- PARALLEL CAPABLE

% POWER OUTPUT 100% 75% 50% 25% DIGITAL DATA CENTER 0% AUTOMATIC ROTATING DIGITAL DISPLAY F9.31 18.5 16:55 551 0 P1.21 FUEL LEVEL (Liters) VOLTAGE LIFETIME RUN HOURS POWER OUTPUT (kW) REMAINING RUN TIME

% FUEL

## • LED DISPLAY

Precise readings to keep you in the know.

## HIGHLY PORTABLE

Telescoping handle and heavy-duty wheels

#### 3-YEAR WARRANTY

Lifetime tech support, EPA, USFS, and CARB Compliant (Legal for sale in California)



# **Onan P4500i**

#### **Inverter Generator Features and Specifications**

- Fuel efficient, 3.4 gallon fuel tank that runs 18 hrs at 25% load
- Very quiet, double-insulated acoustic enclosure and low tone mufflers to reduce operating noise
- 98 Lbs, lighter than competitor inverters of equal power
- Two 5V USB ports for charging sensitive electronics such as phones or tablets
- RV and camper ready with 30A TT-30R outlet
- Push button electric start and remote start
- Telescoping handle for easy transportation
- Dependable 7.3 HP 224cc OHV 4-Stoke engine
- Parallel capable with another inverter generator to reach 50A of power

Part Number	A058U955	
Gasoline Peak Watts	4500	
Gasoline Running Watts	3700	
Peak Amps at 120V	37.5 amps	
Running Amps at 120V	30.8 amps	
AC Voltage	120 Volts	
DC Voltage	5 Volts	
AC Frequency	60 Hz	
Parallel Capable	Yes	
Engine Horse Power (HP)	7.3 HP	
Total Harmonic Distortion (THD)	<3%	
Automatic Voltage Regulator (AVR)	Yes	
Starting System	Electric, Remote, Recoil	
Battery Included	Yes	
Battery Charger Included	Yes	
Remote Start Fob Included	Yes	
	(paired at factory)	
Remote Start Distance (yards/meters)	109 yd. (100 m.)	
Engine Displacement	224cc	
Engine Brand	Ducar	
Engine Type	OHV 4 Stroke	
Engine Speed	Variable	
Engine RPM	Max 3600	
Operational Volume	As low as 52 dBA	
Spark Plug (included)	Torch E6RTC	
Carburetor Kit Required to Operate at Altitude	Yes, above 2000ft	
Economy Mode Switch	Yes	
Built-in Inverter	Yes	
Engine Lubrication	Splash	
Recommended Oil	SAE 10W30	
Oil Bottle Size (included)	.6 qt. (20.3 oz.)	
Oil Capacity (Quarts/Ounces)	.6 qt. (20.3 oz.)	
Low Oil Shutdown	Automatic	
Fuel Type	Unleaded Gasoline, 10% Ethanol or less	
Fuel Shut Off	Manual	
Fuel Tank Material	Steel	
Fuel Tank Capacity (Gallons/Liters)	3.4 gal. (12.8 L)	
Run Time at %25 Load (hrs.)	18 hrs.	
· · · /		

Run Time at %50 Load (hrs.)	15 hrs.	
Gasoline Fuel Gauge	Yes	
Choke type	Automatic	
AC Outlets	(1) 120V 30A (TT-30R) (1) Duplex 120V 20A (5-20R)	
DC Outlets	(2) 5V USB ports	
Ground	Floating Neutral	
Covered Outlets	Yes	
Transfer Switch Ready	No	
GFCI Outlets	No	
LED Data Center	Yes	
RV Ready Outlet	Yes	
Overload Protection (circuit breaker)	Yes	
Handle Style	Telescoping Handle	
Emissions	EPA, CARB	
Canada CSA Compliant	No	
Wheel Kit Included	Yes (assembled)	
Wheel Size	5.5 in. Diameter, 1.5 in. Thick	
Spark Arrestor	Yes	
Residential Warranty	3 Years	
Commercial Warranty	1 Year	
Assembled Length in. (mm)	24.5 in. (622 mm)	
Assembled Width in. (mm)	18.25 in. (463 mm)	
Assembled Height in. (mm)	20.5 in. (520 mm)	
Carton Length in. (mm)	30.3 in. (768 mm)	
Carton Width in. (mm)	19.5 in. (495 mm)	
Carton Height in. (mm)	21 in. (533 mm)	
Dry Unit Weight Ib. (kg)	98 lb. (44 kg)	
Shipping Weight Ib. (kg)	104 lb. (47 kg)	

#### cummins.com

0	Instagram.com/Cummins
y	Twitter.com/Cummins
f	Facebook.com/Cummins
	YouTube.com/Cummins

